

Specifications

Model		L3200 (Rear foldable ROPS model)	
		DT (4WD)	
Engine		D1703-MA-E2A	
Model		D1703-MA-E2A	
Type (Make : Kubota)		Vertical liquid-cooled 4-cycle diesel, Indirect injection (E-TVCS)	
Engine gross power*	kW (PS)	24.6 (33.4)@2500 rpm	
PTO power*	kW (PS)	21.3 (29.0)@2500 rpm	
No. of cylinders		3	
Bore & stroke	mm	87×92.4	
Total displacement	cm ³	1647	
Battery		12V.RC : 123min, CCA : 490A	
Fuel tank capacity	ℓ	34	
PTO		Live-continuous running	
Rear PTO (540 rpm)			
Hydraulic		22.2	
Pump capacity (main)	ℓ/min.		
	(PS) ℓ/min.	13.5	
3-point hitch		Category I	
Lift control type		Position control	
Max. lift force At lift point	kg	906	
	At 610mm behind lift point	kg 651	
Travelling system		Sliding gear & constant mesh 8F/4R	
Transmission			
Steering		Integral power steering	
Brakes		Mechanical wet disk type	
Clutch		Dry-type dual stage	
Rear differential lock		Standard	
Tyre size	AG Standard	Front / Rear	7-16 R1 / 11.2-24 R1
	AG Option	Front / Rear	7.5L-15 / 320/70R24
	TURF Option	Front / Rear	212/80-D15 / 355/80-D20
Travelling speeds w/standard AG tyres		Forward	Reverse
At rated engine speed		km/h 1.6-19.7	2.2-7.1
Maximum speed		km/h Forward 21.3	
Dimensions & weight		2810	
Overall length (w/o 3P)		mm	
Overall width (min. tread)		mm 1290	
Overall height (w/ ROPS)		mm 2460	
Wheelbase		mm 1610	
Min. ground clearance (Front axle)		mm 345	
Tread		mm 1085	
(STD Tyres)	Front		
	Rear	mm 1015, 1115, 1195, 1295	
Min. turning radius (w/ brake)		m 2.5	
Weight (w/ ROPS)		kg 1210	
Optional equipment		Front bumper weights, Aux. control valve	

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

* Manufacture's estimate

©2006 Kubota Corporation



KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.
 Phone Thame (01844) 214500 Fax (01844) 216685
 Web site: <http://www.kubota.co.uk/>
 E-mail: sales@kubota.co.uk

Cat.No.3184-01-UK Printed in Japan.D.REX.'06-AUG.