

				STV-32	STV-36	STV-40
Engine	Model			D1503M	D1703M	D1803M
	Type			E-TVCS water cooled, 4-cycle, 3-cyl diesel		
	Engine Power	ECER-24	kW (PS)	22.8 (31.0)	25.5 (34.7)	28.2 (38.3)
		SAE Gross	kW (HP)	24.1 (32.3)	26.8 (35.9)	29.5 (39.5)
	PTO Power		kW (PS)	17.7 (24.1)	20.2 (27.5)	22.8 (31.0)
	Total Displacement		cc	1499	1647	1826
	Rated Revolution		rpm	2700		
	Fuel Tank Capacity		ltr	29.5		
Power Take-Off	Rear PTO-Revolution			1st (Engine) 540 rpm (@2670 rpm) / 2nd (Engine) 800 rpm (@2717 rpm)		
	Mid PTO-Revolution			2500 rpm (@2734 rpm)		
Transmission	Type			HST: 3 Range		
	Travelling Speed / Fwd		km/hr	0--30.0 (w/9.5--22 tire)		
	Travelling Speed / Rev		km/hr	0--21.7 (w/9.5--22 tire)		
	Clutch			Single Dry Disc		
	Brake			Wet Disc Type		
	Rear Diff. Lock			Equipped		
	Bi-Speed			Equipped		
Steering				Hyrdostatic Type Power Steering		
Tyre	Front			Turf 24x8.50--14	Farm 6.00--12	Industry 23x8.50--14
	Rear			Turf 13.6--16	Farm 9.5--22	Industry 12.4--16
Dimensions (w/Farm Tyres)	Overall Length		mm	2860 (From front hitch)		
	Overall Width		mm	1310 Turf, 1220 Farm, 1480 Industry		
	Overall Height (w/ROPS, w/CAB)		mm	2340/2150 Turf, 2350/2160 Farm, 2335/2145 Industry		
	Wheel Base		mm	1610		
	Tread	Front	mm	1030 Turf, 1030 Farm, 1040 Industry		
		Rear	mm	965/1055 Turf, 950/1070 Farm, 1150 Industry		
	Ground Clearance		mm	225 Turf	235 Farm	220 Industry
	Weight (w/ROPS)		kgf	995 Turf	975 Farm	1025 Industry
	Weight (w/CAB)		kgf	1155 Turf	1135 Farm	1185 Industry
Turning Radius (w/o Brake)				2.5 m w/Bi-Speed engaged w/o barke		
Hydraulics	Pump Capacity		ltr/min	23		
	Relief Valve Pressure		kgf/cm2	173		
	Max Lifint Capacity (at end)		kgf	1150		
	Control Valve			Position Control System		
	Hydraulic Outlet			Mid		
	Auxillar Control Valve			Single/Double acting changeable x1, Double acting x1, Single acting x1 (Triple valve)		
Equipment	Seat			High Back		
	Cruise Control			Notch Type		
	Instrument Panel PTO Lamp			Equipped		
	Instrument Panel Parking Brake Lamp			Equipped		
	PTO Protector			Flip-Up		