

## Specifications

Model		B1410	B1610		
Engine	Make	Kubota			
	Type	E-TVCS, indirect injection, vertical, liquid cooled, 4 cycle diesel			
	DIN power	kW (PS)	9.6 (13.0)	10.7 (14.5)	
	SAE power	kW (HP)	10.3 (14.0)	11.7 (16.0)	
	PTO power	kW (PS)	8.1 (11.0)	9.2 (12.5)	
	No. of cylinders		3	3	
	Total displacement	cm <sup>3</sup>	656	719	
	Muffler		Fully enclosed		
	Air cleaner		Fully enclosed, dry paper element		
	Fuel tank	ℓ (imp. gal)	13 (2.86)		
Drive train	Driving method	4WD			
	Transmission speed	F6R2			
	max. travelling speed	km/h (mph)	with standard farm tyre	15.2 (9.4)	16.2 (10.1)
	Brake type		Wet disc		
PTO	PTO type	Transmission driven with one way clutch			
	Rear PTO speed	rpm	540 /1000		
	Mid PTO speed	rpm	2545		
<b>Hydraulic system</b>					
	Pump capacity	ℓ/min (imp. gpm)	14.1 (3.1)		
	Lift capacity (lower link)	kg (N, lbs.)	540 (5292, 1190)		
	Hydraulic circuit changeover unit		Standard		
Dimensions	Overall length (w/o 3P)	mm (in.)	2035 (80.1)		
	Overall width (min tread)	mm (in.)	with standard farm tyre	932 (36.7)	927 (36.5)
	Overall height (steering)	mm (in.)	1235 (48.6)		1255 (49.4)
	Wheelbase	mm (in.)	1270 (50)		
	Ground clearance	mm (in.)	250 (9.8)		270 (10.6)
	Tread (front)	mm (in.)	778 (30.6)	with standard farm tyre	767 (30.2)
	Tread (rear)	mm (in.)	711-1031 (28.0-40.6)		
	Weight*	kg (lbs.)	510 (1124)		522 (1151)
	Tyre Farm	front	4.5-10		5-12
		rear	7-16		8-16
	Turf	front	20×8.00-10		20×8.00-10
		rear	212 / 80D-15		212 / 80D-15
	Turning radius (with 4WD brake)	m (in.)	1.8 (70.9)		
Other	Steering	Manual			
	Water temp. gauge	Standard			
	Fuel gauge	Standard			
	Tachometer	Standard			
	Operator deck	Semi flat			
Mower cutting width	mm (in.)	1219 (48)**			

The company reserves the right to change the above specifications without notice.

\*Manufacture's estimate.

\*\*Specifications may vary among markets.

\*\*Mower deck can not attach tractor with farm tyre 5-12, 8-16.

©2006 Kubota Corporation



### KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.  
 Phone Thame (01844) 214500 Fax (01844) 216685  
 Web site: <http://www.kubota.co.uk/>  
 E-mail: [sales@kubota.co.uk](mailto:sales@kubota.co.uk)